PRODUCT SPECIFICATION

ICL AMERICA LIMITED

Product:	*PVC 150 RT x B Black*
Product Construction:	Solid Woven 150 lb rated polyester, Black Standard PVC, Roughtop by Brushed
Color:	Black
Compound Formulation:	Thermoplastic Low Durometer Std.. PVC
Durometer	65 +/- Shore A
Nominal Overall Gauge, inches: **mm:**	0.290" +/- 10% 7.4 mm. +/- 10%
Nominal Weight, lbs/ft^2: **kg/m^2:**	1.2 lbs/ft2 +/- 10% 5.8 kg/m2 +/- 10%
Rated Working Tension:	150 lbs/inch / 26 N/mm. @ <2%
Top Cover Surface:	Roughtop
Bottom Cover Surface:	Brushed
Minimum Pulley Diameter (inches/mm):	2.5 inches / 64 mm.
Temperature Range:	0º to 180º F. / -18º to 82ºC.
Transverse Rigidity:	N/A
Special Standards:	N/A
Cover Coefficient of Friction, Steel: **Cardboard:**	1.3, nominal 0.3, nominal
Bottom Coefficient of Friction, Steel: **Cardboard:**	0.9, maximum 0.4, maximum
Production Width(s):	72"/1829mm.
Typical Applications:	Package handling, general conveying, moderate incline/decline applications up to 28 degrees.
Specification Date:	*10/29/2015*

Note: ICL AMERICA, LTD., provides information, both written and verbal, for its products which it believes to be both accurate and representative of the products themselves. This information is based on laboratory tests, Quality Control Reports, and previous experience with these products. This general information is offered as a service only and is not meant as an expression of warranty or the suitability of the product for a particular application.
ICL AMERICA, LTD., does not assume any liability whatsoever in regard to use of the product or its fitness for use in a given application.
The buyer of ICL AMERICA's products must determine for themselves the suitability of such products for a given purpose of the buyer.
ICL AMERICA, LTD., reserves the right to alter the technical specification of this product without prior notice.

Contact: 516-792-3674 **sales@iclamerica.com** **www.iclamerica.com**